

# ENSTO

**PRODUCT SPECIFICATION**

2020-02-24



6418677446023

IPC / Bare connector

SLIP12.127

---

Code SLIP12.127  
 GTIN 6418677446023  
 Name IPC / Bare connector  
 Al/Cu 10-70 mm<sup>2</sup> to Al/Cu 1.5-50 mm<sup>2</sup>  
 Description SLIP12.127 is for all connections of  
 uninsulated aluminium or copper main  
 and insulated branch conductors up to  
 1000 VAC. Equipped with shear head  
 screw.

Vendor



## Technical specification

---

### Others

ETIM Class: EC001062

### Certificates

Connector class: A2  
 Standards: EN 50483-4:2009

### Features

Bolt: M8x50

### Mechanical

Tightening torque Nm: 23,5 Nm

### Electrical values

Highest system voltage: 1 kV

## ETIM 7

---

### Etim

Clamping channel opening branch  
 conductor: Closed

Clamping channel opening main conductor: Closed

Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	1,5 ... 50 mm <sup>2</sup>
Nominal cross section branch conductor SM/RM:	1,5 ... 50 mm <sup>2</sup>
Nominal cross section main conductor SE:	10 ... 70 mm <sup>2</sup>
Nominal cross section main conductor SM:	10 ... 70 mm <sup>2</sup>
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

## Packaging

---

### Pallet package

Unit:	PCE
Package size:	2700
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

### Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	165 mm
Volume:	16,5165 l