

# SIEMENS

## Data sheet for SINAMICS V20



Figure similar

MLFB-Ordering data                      6SL3210-5BE22-2CV0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Rated data	General tech. specifications																																																		
<div>Input</div> <table><tr><td>Number of phases</td><td>3 AC</td></tr><tr><td>Line voltage</td><td>380 ... 480 V -15 % +10 %</td></tr><tr><td>Line frequency</td><td>47 ... 63 Hz</td></tr></table> <div>Output</div> <table><tr><td>Number of phases</td><td>3 AC</td></tr><tr><td>Rated voltage</td><td>400 V</td></tr><tr><td>Rated power (HO)</td><td>2.20 kW / 3.00 hp</td></tr><tr><td>Rated power (LO)</td><td>2.20 kW / 3.00 hp</td></tr><tr><td>Rated current (HO)</td><td>5.60 A</td></tr><tr><td>Rated current (LO)</td><td>5.60 A</td></tr><tr><td>Rated current (HO) at 480V</td><td>4.80 A</td></tr><tr><td>Rated current (LO) at 480V</td><td>4.80 A</td></tr><tr><td>Pulse frequency</td><td>4.00 kHz</td></tr><tr><td>Output frequency</td><td>0 ... 550 Hz</td></tr></table>	Number of phases	3 AC	Line voltage	380 ... 480 V -15 % +10 %	Line frequency	47 ... 63 Hz	Number of phases	3 AC	Rated voltage	400 V	Rated power (HO)	2.20 kW / 3.00 hp	Rated power (LO)	2.20 kW / 3.00 hp	Rated current (HO)	5.60 A	Rated current (LO)	5.60 A	Rated current (HO) at 480V	4.80 A	Rated current (LO) at 480V	4.80 A	Pulse frequency	4.00 kHz	Output frequency	0 ... 550 Hz	<table><tr><td>Power factor <math>\lambda</math></td><td>0.72</td></tr><tr><td>Offset factor <math>\cos \varphi</math></td><td>0.95</td></tr><tr><td>Efficiency <math>\eta</math></td><td>0.98</td></tr><tr><td>Filter class (integrated)</td><td>Class A</td></tr></table> <div>Ambient conditions</div> <table><tr><td>Cooling</td><td>External fan</td></tr><tr><td>Installation altitude</td><td>1000 m (3281 ft)</td></tr></table> <div>Ambient temperature</div> <table><tr><td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr><tr><td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr></table> <div>Relative humidity</div> <table><tr><td>Max. operation</td><td>95 %</td></tr></table> <div>Communication</div> <table><tr><td>Communication</td><td>USS, Modbus RTU</td></tr></table> <div>Standards</div> <table><tr><td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr><tr><td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr></table>	Power factor $\lambda$	0.72	Offset factor $\cos \varphi$	0.95	Efficiency $\eta$	0.98	Filter class (integrated)	Class A	Cooling	External fan	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %	Communication	USS, Modbus RTU	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3
Number of phases	3 AC																																																		
Line voltage	380 ... 480 V -15 % +10 %																																																		
Line frequency	47 ... 63 Hz																																																		
Number of phases	3 AC																																																		
Rated voltage	400 V																																																		
Rated power (HO)	2.20 kW / 3.00 hp																																																		
Rated power (LO)	2.20 kW / 3.00 hp																																																		
Rated current (HO)	5.60 A																																																		
Rated current (LO)	5.60 A																																																		
Rated current (HO) at 480V	4.80 A																																																		
Rated current (LO) at 480V	4.80 A																																																		
Pulse frequency	4.00 kHz																																																		
Output frequency	0 ... 550 Hz																																																		
Power factor $\lambda$	0.72																																																		
Offset factor $\cos \varphi$	0.95																																																		
Efficiency $\eta$	0.98																																																		
Filter class (integrated)	Class A																																																		
Cooling	External fan																																																		
Installation altitude	1000 m (3281 ft)																																																		
Operation	-10 ... 60 °C (14 ... 140 °F)																																																		
Storage	-40 ... 70 °C (-40 ... 158 °F)																																																		
Max. operation	95 %																																																		
Communication	USS, Modbus RTU																																																		
Compliance with standards	CE, cULus, C-Tick (RCM), KC																																																		
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																																																		

Overload capability
Low Overload (LO)
110 % rated output current for 60 s, cycle time 300 s
High Overload (HO)
150 % rated output current for 60 s, cycle time 300 s

# SIEMENS

## Data sheet for SINAMICS V20

MLFB-Ordering data                      6SL3210-5BE22-2CV0



Figure similar

Mechanical data		Connections	
Mounting position	Wall mounting / side-by-side mounting	Max. motor cable length	
Degree of protection	IP20 / UL open type	Shielded	10 m (33 ft)
Size	FSA	Unshielded	50 m (164 ft)
Net weight	1.10 kg ( 2.43 lb )		
Width	90.0 mm ( 3.54 in )		
Height	166.0 mm ( 6.54 in )		
Depth	145.5 mm ( 5.73 in )		
Inputs / outputs			
Standard digital inputs			
Number	4		
Digital outputs			
Number as relay changeover contact	1		
Number as transistor	1		
Analog inputs			
Number	2 (Can be used as additional digital input)		
Analog outputs			
Number	1		