


Zacisk przyłączeniowy 16-120mm², do 5mm
Typ AKU120/5
Catalog No. 107190

Program dostaw

Asortyment			System 60-mm Compact-System
Funkcja podstawowa			Technika przyłączy i połączeń
Grupa asortymentowa			Uniwersalne zaciski przyłączeniowe
Opis			z wbudowaną sprężyną ustalającą, otwartym obszarem zacisku i śrubą zaciskową zabezpieczoną przed zgubieniem
Terminal area W x H		mm	17 x 15
Szerokość		mm	23.5
Znamionowy prąd pracy	I _e	A	440
Przewód			16 - 120 mm ² AWG 4 - MCM 250. zaciskane bezpośrednio:   # 4 x 16 x 0,8 mm lub 6 x 16 x 0,8 mm lub 10 x 16 x 0,8 mm
Stosowane do			All 5 mm thick flat busbars
Wskazówki  round conductor, solid  Flexible, round conductor with correctly crimped ferrule Round conductor, stranded  Sector conductor, solid Sector conductor, stranded # CU band  CU busbar			

Aprobaty

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

