








Zacisk przyłączeniowy 16-70mm², 10 mm

Typ **AKU70/10**
 Catalog No. **107193**

Program dostaw

Asortyment			System 60-mm System 185-mm Compact-System
Funkcja podstawowa			Technika przyłączy i połączeń
Grupa asortymentowa			Uniwersalne zaciski przyłączeniowe
Opis			z wbudowaną sprężyną ustalającą, otwartym obszarem zacisku i śrubą zaciskową zabezpieczoną przed zgubieniem
Terminal area W x H		mm	14 x 14
Szerokość		mm	20.5
Znamionowy prąd pracy	I _e	A	400
Przewód			16 - 70 mm ² AWG 4 - AWG 2/0. zaciskane bezpośrednio:   # 2x (3 x 9 x 0,8 mm) lub 6 x 9 x 0,8 mm
Stosowane do			All 10 mm thick flat busbars
Wskazówki			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

Aprobaty

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

Wymiary

