



Figure similar

MLFB-Ordering data

6SL3210-5BE13-7CV0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																																																		
<div>Input</div> <table><tr><td>Number of phases</td><td>3 AC</td></tr><tr><td>Line voltage</td><td>380 ... 480 V -15 % +10 %</td></tr><tr><td>Line frequency</td><td>47 ... 63 Hz</td></tr></table> <div>Output</div> <table><tr><td>Number of phases</td><td>3 AC</td></tr><tr><td>Rated voltage</td><td>400 V</td></tr><tr><td>Rated power (HO)</td><td>0.37 kW / 0.50 hp</td></tr><tr><td>Rated power (LO)</td><td>0.37 kW / 0.50 hp</td></tr><tr><td>Rated current (HO)</td><td>1.30 A</td></tr><tr><td>Rated current (LO)</td><td>1.30 A</td></tr><tr><td>Rated current (HO) at 480V</td><td>1.30 A</td></tr><tr><td>Rated current (LO) at 480V</td><td>1.30 A</td></tr><tr><td>Pulse frequency</td><td>4.00 kHz</td></tr><tr><td>Output frequency</td><td>0 ... 550 Hz</td></tr></table>	Number of phases	3 AC	Line voltage	380 ... 480 V -15 % +10 %	Line frequency	47 ... 63 Hz	Number of phases	3 AC	Rated voltage	400 V	Rated power (HO)	0.37 kW / 0.50 hp	Rated power (LO)	0.37 kW / 0.50 hp	Rated current (HO)	1.30 A	Rated current (LO)	1.30 A	Rated current (HO) at 480V	1.30 A	Rated current (LO) at 480V	1.30 A	Pulse frequency	4.00 kHz	Output frequency	0 ... 550 Hz	<table><tr><td>Power factor λ</td><td>0.72</td></tr><tr><td>Offset factor $\cos \varphi$</td><td>0.95</td></tr><tr><td>Efficiency η</td><td>0.98</td></tr><tr><td>Filter class (integrated)</td><td>Class A</td></tr></table> <div>Ambient conditions</div> <table><tr><td>Cooling</td><td>convection cooling</td></tr><tr><td>Installation altitude</td><td>1000 m (3281 ft)</td></tr></table> <div>Ambient temperature</div> <table><tr><td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr><tr><td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr></table> <div>Relative humidity</div> <table><tr><td>Max. operation</td><td>95 %</td></tr></table> <div>Communication</div> <table><tr><td>Communication</td><td>USS, Modbus RTU</td></tr></table> <div>Standards</div> <table><tr><td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr><tr><td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr></table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98	Filter class (integrated)	Class A	Cooling	convection cooling	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %	Communication	USS, Modbus RTU	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3
Number of phases	3 AC																																																		
Line voltage	380 ... 480 V -15 % +10 %																																																		
Line frequency	47 ... 63 Hz																																																		
Number of phases	3 AC																																																		
Rated voltage	400 V																																																		
Rated power (HO)	0.37 kW / 0.50 hp																																																		
Rated power (LO)	0.37 kW / 0.50 hp																																																		
Rated current (HO)	1.30 A																																																		
Rated current (LO)	1.30 A																																																		
Rated current (HO) at 480V	1.30 A																																																		
Rated current (LO) at 480V	1.30 A																																																		
Pulse frequency	4.00 kHz																																																		
Output frequency	0 ... 550 Hz																																																		
Power factor λ	0.72																																																		
Offset factor $\cos \varphi$	0.95																																																		
Efficiency η	0.98																																																		
Filter class (integrated)	Class A																																																		
Cooling	convection cooling																																																		
Installation altitude	1000 m (3281 ft)																																																		
Operation	-10 ... 60 °C (14 ... 140 °F)																																																		
Storage	-40 ... 70 °C (-40 ... 158 °F)																																																		
Max. operation	95 %																																																		
Communication	USS, Modbus RTU																																																		
Compliance with standards	CE, cULus, C-Tick (RCM), KC																																																		
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																																																		

Overload capability
Low Overload (LO)
110 % rated output current for 60 s, cycle time 300 s
High Overload (HO)
150 % rated output current for 60 s, cycle time 300 s

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data 6SL3210-5BE13-7CV0



Figure similar

Mechanical data		Connections	
Mounting position	Wall mounting / side-by-side mounting	Max. motor cable length	
Degree of protection	IP20 / UL open type	Shielded	10 m (33 ft)
Size	FSA	Unshielded	50 m (164 ft)
Net weight	1.00 kg (2.20 lb)		
Width	90.0 mm (3.54 in)		
Height	150.0 mm (5.91 in)		
Depth	145.5 mm (5.73 in)		

Inputs / outputs	
Standard digital inputs	
Number	4
Digital outputs	
Number as relay changeover contact	1
Number as transistor	1
Analog inputs	
Number	2 (Can be used as additional digital input)
Analog outputs	
Number	1