

## Conductor marker carrier - PATG 0/15 - 1013740

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 0.6 ... 1.2 mm, lettering field size: 15 x 4 mm

### Your advantages

- ✓ The corresponding UC-WMT ..., US-WMT ..., UCT-WMT ... and EMT ... insert labels are used for marking
- ✓ The PATG ... collar is a captive marker carrier
- ✓ These conductor marking systems consist of marker carriers and insert labels
- ✓ Can be used to mark conductors with a diameter of 0.6 ... 50 mm



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 1000 pc                                                                                                 |
| Minimum order quantity | 1000 pc                                                                                                 |
| GTIN                   | <br>4 017918 013936 |
| GTIN                   | 4017918013936                                                                                           |

### Technical data

#### Dimensions

|                |                   |
|----------------|-------------------|
| Length (b)     | 15 mm             |
| Width (a)      | 5 mm              |
| Cable diameter | 0.6 mm ... 1.2 mm |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -50 °C ... 80 °C |
|---------------------------------|------------------|

#### General

|                                        |               |
|----------------------------------------|---------------|
| Color                                  | transparent   |
| Type                                   | Profile       |
| Components                             | Silicone-free |
| Flammability rating according to UL 94 | V0            |

# Conductor marker carrier - PATG 0/15 - 1013740

## Technical data

### General

|                                                                     |                      |
|---------------------------------------------------------------------|----------------------|
| Material                                                            | PVC                  |
| RoHS compliant                                                      | Yes                  |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result                                                              | Test passed          |
| Marking mounting type                                               | slide-on             |

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400401 |
| eCl@ss 4.0    | 27061700 |
| eCl@ss 4.1    | 27061700 |
| eCl@ss 5.0    | 27400400 |
| eCl@ss 5.1    | 27400400 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149153 |
| eCl@ss 8.0    | 27400401 |
| eCl@ss 9.0    | 27400401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC002248 |
| ETIM 6.0 | EC001530 |
| ETIM 7.0 | EC001530 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131504 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |
| UNSPSC 20.0   | 39131504 |
| UNSPSC 21.0   | 39131504 |

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>