

Coding element - HC-CST-MOD - 1636127


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coding peg for coding up to 16 connectors, for HC Modular



Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 963057
GTIN	4017918963057

Technical data

Dimensions

Length	23.2 mm
Width	4.3 mm
Height	4.3 mm

General

Note	Prevents most cases of the connector being inserted at an angle
Material	Steel, galvanized
Color	silver
Note	Prevents most cases of the connector being inserted at an angle
Assembly instructions	Coding pins and sockets are required for the modules HC-M-DSUB... and HC-M-25-MOD...


Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings


Coding element - HC-CST-MOD - 1636127

Dimensional drawing



Dimensional drawing


Circuit diagram



Coding for housings with two contact inserts

Coding element - HC-CST-MOD - 1636127

Circuit diagram



Coding for housings with one contact insert

Classifications

eCl@ss

eCl@ss 10.0.1	27440203
eCl@ss 11.0	27440203
eCl@ss 4.0	27140800
eCl@ss 4.1	27140800
eCl@ss 5.0	27143400
eCl@ss 5.1	27143400
eCl@ss 6.0	27269200
eCl@ss 7.0	27440203
eCl@ss 8.0	27440203
eCl@ss 9.0	27440203

ETIM

ETIM 2.0	EC001121
ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002311
ETIM 6.0	EC002311
ETIM 7.0	EC002311

Coding element - HC-CST-MOD - 1636127

Classifications

UNSPSC

UNSPSC 6.01	30211817
UNSPSC 7.0901	39121416
UNSPSC 11	43172601
UNSPSC 12.01	39121522
UNSPSC 13.2	27112301
UNSPSC 18.0	27112301
UNSPSC 19.0	27112301
UNSPSC 20.0	27112301
UNSPSC 21.0	27112301

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>