

SITOR fuse switch 10x 38, Up to 32 A, 690 V AC



Model	
product brand name	SITOR
product designation	SITOR fuse switch disconnecter
design of the operating mechanism	others
General technical data	
number of poles	1
size of fuse link	Other
usage category	According to IEC 60947-3; AC 22B/32 A/400 V; AC22B/10 A/690 V
size of the fuse link	10 x 38 mm
operating voltage	
• at AC / rated value / maximum	690 V
• at DC / rated value / maximum	800 V
Protection class	
protection class IP / on the front	Other
Current	
continuous current / rated value	32 A

Main circuit	
operating current / rated value	32 A
Suitability	
suitability for use	
• main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
Product function	
product function / fuse monitoring	No
Short circuit	
conditional short-circuit current (I _q) / rated value	50 kA
Connections	
connectable conductor cross-section / solid	
• minimum	1.5 mm ²
• maximum	25 mm ²
connectable conductor cross-section / stranded	
• minimum	1.5 mm ²
• maximum	25 mm ²
type of electrical connection / for main current circuit	screw-type terminals
Mechanical Design	
height	58 mm
depth	85 mm
mounting type	
• floor mounting	No
• front mounting	Yes
• rail mounting	No
net weight	51 g
Certificates	
reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval					Declaration of Conformity
 CCC	 CSA	 UL	 UR	Miscellaneous	 EG-Konf.

other
Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1091>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1091>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1091

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



