

SITOR fuse switch 10x 38, Up to 32 A, 690 V AC, 3-pole



Figure similar

Model	
product brand name	SITOR
product designation	SITOR fuse switch disconnecter
design of the operating mechanism	others
General technical data	
number of poles	3
size of fuse link	Other
usage category	According to IEC 60947-3; AC 22B/32 A/400 V; AC22B/10 A/690 V
size of the fuse link	10 x 38 mm
operating voltage	
<ul style="list-style-type: none"> • at AC / rated value / maximum • at DC / rated value / maximum 	<p>690 V</p> <p>800 V</p>
Protection class	
protection class IP / on the front	Other
Current	

continuous current / rated value	32 A
Main circuit	
operating current / rated value	32 A
Suitability	
suitability for use	
• main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
Product function	
product function / fuse monitoring	No
Short circuit	
conditional short-circuit current (I _q) / rated value	50 kA
Connections	
connectable conductor cross-section / solid	
• minimum	1.5 mm ²
• maximum	25 mm ²
connectable conductor cross-section / stranded	
• minimum	1.5 mm ²
• maximum	25 mm ²
type of electrical connection / for main current circuit	screw-type terminals
Mechanical Design	
height	58 mm
depth	85 mm
mounting type	
• floor mounting	No
• front mounting	Yes
• rail mounting	No
net weight	155 g
Certificates	
reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F



CCC



CSA



UL



UR

[Miscellaneous](#)

EG-Konf.

other[Miscellaneous](#)**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1093>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3NC1093>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1093**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>



