

Residual current operated circuit breaker, 4-pole, Type AC, In: 40 A, 30 mA, Un AC: 400 V, N left



Model	
product brand name	SENTRON
product designation	RCCB
design of the product	Instantaneous
product variations	N left
General technical data	
number of poles	4
size of installation devices / acc. to DIN 43880	1
protection against electrical shock	Finger and back-of-hand safe
short-circuit current / of series fuse / maximum permissible	80 A
short-circuit current rating	10 kA
mechanical service life (switching cycles) / typical	10 000
switching function / short-term delayed	No
overvoltage category	III
Supply voltage	
operating current / at AC / rated value	40 A
• supply voltage / at AC / rated value	400 V

• supply voltage / for testing equipment / minimum	195 V
operating frequency	50 Hz
supply voltage frequency	
• rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
switching capacity current	
• acc. to EN 60898 / rated value	0.8 kA
• according to IEC 61008-1 / rated value	0.8 kA
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	3.9 W
• maximum	11.7 W
Current	
tripping residual current / rated value	30 mA
type of fault current	AC
let-through current / permissible	5 200 kA
I ² t value / permissible	58 000 A ² ·s
operating current	
• at 40 °C / rated value	40 A
• at 45 °C / rated value	38.1 A
• at 50 °C / rated value	35.59 A
• at 55 °C / rated value	32.29 A
• at 60 °C / rated value	28.19 A
• at 65 °C / rated value	23.3 A
• at 70 °C / rated value	17.62 A
Product details	
product feature / silicon-free	Yes
product extension / can be installed / supplementary devices	Yes
Connections	
connectable conductor cross-section / solid	
• minimum	0.75 mm ²
• maximum	35 mm ²
connectable conductor cross-section / stranded	
• minimum	0.75 mm ²

• maximum	35 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position / of power supply cord	top or bottom

Mechanical Design

height	90 mm
width	72 mm
depth	70 mm
installation depth	70 mm
number of width units	4
mounting type	DIN rail (REG)
mounting position	any

Environmental conditions

ambient temperature	
• minimum	-25 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28

Certificates

reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	other	Railway
--------------------------	------------------------------	-------	---------



CCC

[Miscellaneous](#)



EG-Konf.

[Miscellaneous](#)

[Vibration and Shock](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)


<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV4344-0KL>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV4344-0KL>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV4344-0KL





Siemens

5SV(3,4)

Format / Size: Hyt

