

Mosaic™ Blanking plates





1. USE

Mosaic blanking plates pre-equipped for fixing of a printed circuit. Fixing with clips.

The mechanisms can be flush-mounted or surface-mounted.

Antimicrobial products:

These products are made of silver-ion based antimicrobial* material. This technology eliminates bacteria, fungi and viruses without creating any immunisation or resistance effects (physical, rather than chemical, destruction).

Particularly suitables for healthcare establishments (hospitals, clinics, nursing homes, laboratories, waiting rooms, etc.) and more generally for areas subject to hygiene restrictions (industrial, shared and restaurant kitchens, waste, etc.).

These products offer an additional way of ensuring the non-proliferation of bacteria, fungi and viruses without interfering with cleaning protocols

2. RANGE

Designation	White	Aluminium	Matt Black	White antimicrobial*	
Blanking plate 1 module	0 770 70	0 792 70	-	0 787 20	
Blanking plate 2 modules	0 770 71	0 792 80	0 791 81L	0 787 21	

3. DIMENSIONS (mm)





Cat. No(s)	А	В	с	D
0 770 70 - 0787 20 - 0 792 70	45	22.5	24.5	8.5
0 770 71 - 0 787 21 - 0 791 81L - 0 792 80	45	45	24.5	8.5



0 770 71

4. TECHNICAL CHARACTERISTICS

4.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 41 Protection against impact: IK 04

4.2 Material characteristics

ABS - White RAL 9003

- White RAL 9003 with antimicrobial* treatment
- Painted Aluminum varnished glittery
- Painted Matt Black satin finish RAL 9017

Halogen-free

UV-resistant

Self-extinguishing: 650°C/30 s

4.3 Climate characteristics

Storage temperature: - 10° C to + 70° C Usage temperature: - 5° C to + 35° C

5. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Resistance to the cleaning products: Hexane (EN 60669-1, methylated spirit, soapy water, diluted ammonia, pure bleach diluted to 10%, windowcleaning products, pre-impregnated wipes.

Resistance to type cleaning hospital: Anios, Surfanios, Bactilysine, Diluted hydrogen peroxide (35 %).

Caution: Always test before using other special cleaning products

6. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing. See e.catalogue.

*Contains silver ions that limit the development of bacteria on the surface