

# Product Environmental Profile

**ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE**






## General information

|                                   |  |
|-----------------------------------|--|
| <b>Representative product</b>     | ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE - S520052-S520702  |
| <b>Description of the product</b> | The main purpose of the Odace socket outlet product is to give a solution for the infrastructures that give access to Electricity till the plug.   |
| <b>Description of the range</b>   | <p>The indicators values of this Odace Socket Outlet can be extrapolated for other Odace Socket outlets : with or without pin earth, flush or not and for all finishing types.</p> <p>The environmental impacts of these referent products are representative of the impacts of the other products of the range which are developed with a similar technology.</p> |
| <b>Functional unit</b>            | Connect/Disconnect during 20 years the plug of a load consuming 16A under a voltage of 250V while protecting the user from direct contact with live parts and with a protection class IP21 in accordance with the standard IEC 60529 and IK04 in accordance with the standard IEC 62262.   |



## Constituent materials

**Reference product mass** 82,15 g including the product, its packaging and additional elements and accessories



|          |       |
|----------|-------|
| Plastics | 64,0% |
| Metals   | 12,0% |
| Others   | 24,0% |



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

## Additional environmental information

The ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE presents the following relevant environmental aspects


|                      |   |
|----------------------|---|
| <b>Manufacturing</b> | Manufactured at a Schneider Electric production site ISO14001 certified   |
| <b>Distribution</b>  | Weight and volume of the packaging optimized, based on the European Union's packaging directive<br>Packaging weight is 21,2 g, consisting of Cardboard (93,1%), Paper (1,2%), PP film (5,7%)<br>Packaging recycled materials is 70% of total packaging mass.<br>Product distribution optimised by setting up local distribution centres   |
| <b>Installation</b>  | The products do not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials are accounted during the installation phase (including transport to disposal).  |
| <b>Use</b>           | The product does not require special maintenance operations.  |
| <b>End of life</b>   | End of life optimized to decrease the amount of waste and allow recovery of the product components and materials<br>No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.<br>Recyclability potential: <b>12%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME). |

## Environmental impacts

|   |   |  |  |  |
|---|---|--|--|--|
| <b>Reference life time</b>              | 20 years  |  |  |  |
| <b>Product category</b>                 | Power socket  |  |  |  |
| <b>Installation elements</b>            | No special components needed  |  |  |  |
| <b>Use scenario</b>                     | The product is in active mode 50% of the time with a power use of 0.3072W (8 A corresponding to 50% of Max current) and off for the other 50% of the time, for 20 years |  |  |  |
| <b>Geographical representativeness</b>  | France  |  |  |  |
| <b>Technological representativeness</b> | The main purpose of the Odace socket outlet product is to give a solution for the infrastructures that give access to Electricity till the plug.                        |  |  |  |
| <b>Energy model used</b>                | <b>Manufacturing</b>  | <b>Installation</b>  | <b>Use</b>   | <b>End of life</b>   |
|   | Spain - Electricity grid mix; AC; consumption mix, at consumer; 230V; ES  | Electricity grid mix; AC; consumption mix, at consumer; 230V; FR | Electricity grid mix; AC; consumption mix, at consumer; 230V; FR | Electricity grid mix; AC; consumption mix, at consumer; 230V; FR |

| Compulsory indicators                            |                                     | ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE - S520052-S520702 |               |              |              |          |             |
|--|-------------------------------------|---|---------------|--------------|--------------|----------|-------------|
| Impact indicators                                | Unit                                | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Contribution to mineral resources depletion      | kg Sb eq                            | 1,16E-05  | 1,02E-05      | 0*           | 0*           | 1,43E-06 | 0*          |
| Contribution to the soil and water acidification | kg SO <sub>2</sub> eq               | 1,20E-02  | 1,04E-03      | 4,84E-05     | 4,97E-06     | 1,09E-02 | 1,95E-05    |
| Contribution to water eutrophication             | kg PO <sub>4</sub> <sup>3-</sup> eq | 1,67E-03  | 6,63E-04      | 1,11E-05     | 1,56E-06     | 9,92E-04 | 6,19E-06    |
| Contribution to global warming                   | kg CO <sub>2</sub> eq               | 3,27E+00  | 3,19E-01      | 1,06E-02     | 1,20E-03     | 2,93E+00 | 1,37E-02    |
| Contribution to ozone layer depletion            | kg CFC11 eq                         | 4,32E-06  | 1,35E-07      | 0*           | 0*           | 4,18E-06 | 4,71E-10    |
| Contribution to photochemical oxidation          | kg C <sub>2</sub> H <sub>4</sub> eq | 7,33E-04  | 9,70E-05      | 3,45E-06     | 3,72E-07     | 6,30E-04 | 1,97E-06    |
| Resources use                                    | Unit                                | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Net use of freshwater                            | m3                                  | 6,95E+01  | 1,52E-01      | 0*           | 0*           | 6,93E+01 | 0*          |
| Total Primary Energy                             | MJ                                  | 2,72E+02  | 4,88E+00      | 1,50E-01     | 0*           | 2,67E+02 | 9,19E-02    |

SCHN-00843-V01.01-EN - PEP ECOPASSPORT® - ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE



| Optional indicators   |                | ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE - S520052-S520702 |               |              |              |          |             |
|---|----------------|---|---------------|--------------|--------------|----------|-------------|
| Impact indicators   | Unit           | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Contribution to fossil resources depletion  | MJ             | 3,78E+01  | 3,89E+00      | 1,49E-01     | 1,52E-02     | 3,37E+01 | 7,39E-02    |
| Contribution to air pollution   | m <sup>3</sup> | 1,61E+02  | 6,22E+01      | 4,51E-01     | 5,59E-02     | 9,75E+01 | 6,80E-01    |
| Contribution to water pollution   | m <sup>3</sup> | 1,92E+02  | 4,11E+01      | 1,74E+00     | 1,78E-01     | 1,48E+02 | 9,00E-01    |
| Resources use   | Unit           | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Use of secondary material   | kg             | 4,93E-02  | 4,93E-02      | 0*           | 0*           | 0*       | 0*          |
| Total use of renewable primary energy resources   | MJ             | 1,96E+01  | 2,29E-01      | 0*           | 0*           | 1,94E+01 | 0*          |
| Total use of non-renewable primary energy resources   | MJ             | 2,53E+02  | 4,65E+00      | 1,50E-01     | 0*           | 2,48E+02 | 9,18E-02    |
| Use of renewable primary energy excluding renewable primary energy used as raw material         | MJ             | 1,95E+01  | 1,70E-01      | 0*           | 0*           | 1,94E+01 | 0*          |
| Use of renewable primary energy resources used as raw material                                  | MJ             | 5,87E-02  | 5,87E-02      | 0*           | 0*           | 0*       | 0*          |
| Use of non renewable primary energy excluding non renewable primary energy used as raw material | MJ             | 2,52E+02  | 3,70E+00      | 1,50E-01     | 0*           | 2,48E+02 | 9,18E-02    |
| Use of non renewable primary energy resources used as raw material                              | MJ             | 9,50E-01  | 9,50E-01      | 0*           | 0*           | 0*       | 0*          |
| Use of non renewable secondary fuels  | MJ             | 0,00E+00  | 0*            | 0*           | 0*           | 0*       | 0*          |
| Use of renewable secondary fuels  | MJ             | 0,00E+00  | 0*            | 0*           | 0*           | 0*       | 0*          |
| Waste categories  | Unit           | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Hazardous waste disposed  | kg             | 9,00E-01  | 7,78E-01      | 0*           | 0*           | 5,52E-03 | 1,17E-01    |
| Non hazardous waste disposed  | kg             | 6,46E+00  | 4,69E-01      | 0*           | 1,10E-03     | 5,99E+00 | 0*          |
| Radioactive waste disposed  | kg             | 8,86E-02  | 2,07E-04      | 0*           | 0*           | 8,84E-02 | 0*          |
| Other environmental information   | Unit           | Total   | Manufacturing | Distribution | Installation | Use      | End of Life |
| Materials for recycling   | kg             | 3,57E-02  | 8,19E-03      | 0*           | 2,02E-02     | 0*       | 7,35E-03    |
| Components for reuse  | kg             | 0,00E+00  | 0*            | 0*           | 0*           | 0*       | 0*          |
| Materials for energy recovery   | kg             | 2,59E-03  | 0*            | 0*           | 0*           | 0*       | 2,59E-03    |
| Exported Energy   | MJ             | 6,31E-05  | 5,93E-06      | 0*           | 5,71E-05     | 0*       | 0*          |

SCHN-00843-V01.01-EN - PEP ECOPASSPORT® - ODACE SOCKET OUTLET 2P+E PIN EARTH, 16 A, SCREWLESS, FLUSH with OUTER PLATE

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version 5.9.3, database version 2020-12 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range, ratios to apply may be provided on request

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

|   |                      |                                     |  |
|---|----------------------|-------------------------------------|--|
| Registration number :   | SCHN-00843-V01.01-EN | Drafting rules                      | PCR-ed3-EN-2015 04 02  |
| Verifier accreditation N°   | VH39                 | Supplemented by                     | PSR-0005-ed2-EN-2016 03 29   |
| Date of issue   | 09/2022              | Information and reference documents | <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a> |
|   |                      | Validity period                     | 5 years  |
| Independent verification of the declaration and data, in compliance with ISO 14025 : 2010                                   |                      |                                     |  |
| Internal  | External             | X                                   |  |
| The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)                                     |                      |                                     |  |
| PEP are compliant with XP C08-100-1 :2016   |                      |                                     |  |
| The elements of the present PEP cannot be compared with elements from another program.                                      |                      |                                     |  |
| Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations » |                      |                                     |  |



Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier  
CS 30323  
F- 92506 Rueil Malmaison Cedex  
RCS Nanterre 954 503 439  
Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

SCHN-00843-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

09/2022