

OPASKI MET - z metalowym zębkiem

materiał: poliamid 6.6, stal nierdzewna

temp. montażu: min. -20°C

temp. pracy: -60°C do +85°C

wytrzymałość dielektryczna: 50 kV/mm²

absorpcja wody: 2,5% (50% R.H., +23°C)

palność: UL-94 V2


tolerancja: ±5%



TYP	 ROZMIAR [mm]	max/min  ŚREDNICA [mm]	 WYTRZYMAŁOŚĆ [kg]	 OPAKOWANIE [szt]	
MET-100MC	100x2,5	24/2	18	100	☐
MET-200MC	200x2,5	55/2	18	100	☐
MET-140IC	140x3,5	36/3	28	100	☐
MET-200IC	200x3,5	55/3	28	100	☐
MET-280IC	280x3,5	80/3	28	100	☐
MET-190STC	186x4,5	51/3	40	100	☐
MET-300STC	290x4,5	80/3	40	100	☐
MET-370STC	360x4,5	103/3	40	100	☐
MET-370HD	360x7,5	101/6	80	50	☐



TRYTYT.COM!



OPASKI MET - z metalowym zębkiem

materiał: poliamid 6.6, stal nierdzewna

temp. montażu: min.-20°C

temp. pracy: -60°C do +85°C

wytrzymałość dielektryczna: 50 kV/mm²

absorpcja wody: 2,5% (50% R.H., +23°C)

palność: UL-94 V2

tolerancja: ±5%



TYP	 ROZMIAR [mm]	 max/min ŚREDNICA [mm]	 WYTRZYMAŁOŚĆ [kg]	 OPAKOWANIE [szt]	
MET-100MW	100x2,5	24/2	18	100	■
MET-200MW	200x2,5	55/2	18	100	■
MET-140IW	140x3,5	36/3	28	100	■
MET-200IW	200x3,5	55/3	28	100	■
MET-280IW	280x3,5	80/3	28	100	■
MET-190STW	186x4,5	51/3	40	100	■
MET-300STW	290x4,5	80/3	40	100	■
MET-370STW	360x4,5	103/3	40	100	■
MET-370HW	360x7,5	101/6	80	50	■



złącz

TRYTYT.COM!