

Specyfikacje



Zdjęcie jest reprezentatywne



Eaton 111892

Eaton Moeller series Power Defense -
Molded Case Circuit Breaker. Circuit-breaker
LZW, 3 p, 50A, C1-A50-I

General specifications

PRODUCT NAME	Eaton Moeller series Power Defense molded case circuit-breaker
---------------------	--

CATALOG NUMBER	111892
-----------------------	--------

EAN	4015081114405
------------	---------------

PRODUCT LENGTH/DEPTH	88 mm
---------------------------------	-------

PRODUCT HEIGHT	145 mm
-----------------------	--------

PRODUCT WIDTH	90 mm
----------------------	-------

PRODUCT WEIGHT	1.014 kg
-----------------------	----------

COMPLIANCES	RoHS conform
--------------------	--------------

CERTIFICATIONS	IEC/EN 60947 IEC VDE 0660
-----------------------	---------------------------------

MODEL CODE	LZMC1-A50-I
-------------------	-------------



Powering Business Worldwide

Delivery program

CIRCUIT BREAKER FRAME TYPE	LZM1
APPLICATION	Use in unearthed supply systems at 690 V
AMPERAGE RATING	50 A
NUMBER OF POLES	Three-pole

Technical data - electrical

VOLTAGE RATING	690 V - 690 V
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS	6000 V
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS	6000 V
RATED OPERATIONAL CURRENT	160 A (380/400 V AC-1, making and breaking capacity) 50 A (660-690 V AC-3, making and breaking capacity) 50 A (415 V AC-3, making and breaking capacity) 160 A (690 V AC-1, making and breaking capacity) 125 A (415 V AC-1, making and breaking capacity)
INSTANTANEOUS CURRENT SETTING (II) - MIN	300 A
INSTANTANEOUS CURRENT SETTING (II) - MAX	500 A
OVERLOAD CURRENT SETTING (IR) - MIN	40 A
OVERLOAD CURRENT SETTING (IR) - MAX	50 A
SHORT DELAY CURRENT SETTING (ISD) - MIN	0 A
SHORT DELAY CURRENT SETTING (ISD) - MAX	0 A
SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN	300 A
SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX	500 A
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ	55 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ	36 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ	22.5 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 HZ	6 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 240 V, 50/60 HZ	121 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 400/415 V, 50/60 HZ	76 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 440 V, 50/60 HZ	63 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 525 V, 50/60 HZ	24 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 690 V, 50/60 HZ	14 kA
SHORT-CIRCUIT TOTAL BREAKTIME	< 10 ms
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Frame clamp
ISOLATION	300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
OVERVOLTAGE CATEGORY	III
UTILIZATION CATEGORY	A (IEC/EN 60947-2)
POLLUTION DEGREE	3
LIFESPAN, ELECTRICAL	10000 operations at 400 V AC-1 7500 operations at 415 V AC-3 10000 operations at 415 V AC-1 7500 operations at 690 V AC-1

Technical data - mechanical

TYPE	Circuit breaker
RELEASE SYSTEM	Thermomagnetic release
MOUNTING METHOD	Fixed Built-in device fixed built-in technique DIN rail (top hat rail) mounting optional
DEGREE OF PROTECTION	IP20 In the area of the HMI devices: IP20 (basic protection type)
DEGREE OF PROTECTION (IP), FRONT SIDE	IP66 (with door coupling rotary handle) IP40 (with insulating surround)
DEGREE OF PROTECTION (TERMINATIONS)	IP00 (terminations, phase isolator and band terminal) IP10 (tunnel terminal)
PROTECTION AGAINST DIRECT CONTACT	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
SHOCK RESISTANCE	20 g (half-sinusoidal shock 20 ms)
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF OPERATIONS PER HOUR - MAX	120
HANDLE TYPE	Rocker lever
POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Front side
DIRECTION OF INCOMING SUPPLY	As required
STANDARD TERMINALS	Box terminal
TERMINAL CAPACITY (CONTROL CABLE)	0.75 mm ² - 1.5 mm ² (2x) 0.75 mm ² - 2.5 mm ² (1x)
TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)	16 mm ² (1x) at tunnel terminal

Design verification as per IEC/EN 61439 - technical data

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 50 A

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT 13.2 W

TERMINAL CAPACITY (COPPER BUSBAR)	<p>Max. 16 mm x 5 mm direct at switch rear-side connection</p> <p>Min. 12 mm x 5 mm direct at switch rear-side connection</p> <p>M8 at rear-side screw connection</p>
TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)	<p>10 mm² - 16 mm² (1x) direct at switch rear-side connection</p> <p>6 mm² - 16 mm² (2x) at box terminal</p> <p>16 mm² - 95 mm² (1x) at tunnel terminal</p> <p>10 mm² - 16 mm² (1x) at box terminal</p> <p>6 mm² - 16 mm² (2x) direct at switch rear-side connection</p>
TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)	<p>25 mm² - 95 mm² (1x) at tunnel terminal</p> <p>25 mm² (2x) direct at switch rear-side connection</p> <p>25 mm² - 70 mm² (1x) direct at switch rear-side connection</p> <p>25 mm² - 70 mm² (1x) at box terminal</p> <p>25 mm² (2x) at box terminal</p>
TERMINAL CAPACITY (COPPER STRIP)	<p>Min. 2 segments of 9 mm x 0.8 mm at box terminal</p> <p>Max. 9 segments of 9 mm x 0.8 mm at box terminal</p>
CLIMATIC PROOFING	<p>Damp heat, cyclic, to IEC 60068-2-30</p> <p>Damp heat, constant, to IEC 60068-2-78</p>
LIFESPAN, MECHANICAL	20000 operations

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF	Is the panel builder's responsibility.

Additional information

FEATURES	Protection unit
FUNCTIONS	System and cable protection

SPECIAL FEATURES

- Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})
- Rated current = rated uninterrupted current: 50 A

INSULATING MATERIAL

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Do pobrania

	eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-033.eps
CHARACTERISTIC CURVE	eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-039.eps eaton-circuit-breaker-nzm-mccb-characteristic-curve-051.eps
DEKLARACJE ZGODNOŚCI	eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250118en.pdf
INSTRUKCJE MONTAŻU	eaton-circuit-breaker-basic-unit-lzm1-instruction-leaflet-il01203007z.pdf
RYSUNKI	eaton-circuit-breaker-nzm-mccb-dimensions-017.eps eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-006.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie prawa zastrzeżone.

Follow us on social media to get the latest product and support information.

