

Specyfikacje



Zdjęcie jest reprezentatywne



Eaton 171404

Eaton Moeller® series SL7 Strobe light module, red, LED, 24 V

General specifications

PRODUCT NAME	Eaton Moeller® series SL7 Strobe light module
---------------------	---

CATALOG NUMBER	171404
-----------------------	--------

EAN	4015081678242
------------	---------------

PRODUCT LENGTH/DEPTH	73 mm
-----------------------------	-------

PRODUCT HEIGHT	73 mm
-----------------------	-------

PRODUCT WIDTH	73 mm
----------------------	-------

PRODUCT WEIGHT	0.08 kg
-----------------------	---------

COMPLIANCES	CE Marked
--------------------	-----------

CERTIFICATIONS

CSA Certified
cULus Listed
CSA Std. C22.2 No. 94-91
IEC Rated
CSA Class No. NKCR7
CSA Std. C22.2 No. 14-10
UL Listed
UL 508
UL Listed file E29184
CE
IEC/EN 60529
CSA Class No.: NKCR7
UL Category Control No.: NKCR
CSA-C22.2 No. 14-10
UL File No.: E29184
UL report applies to both US and Canada
CSA-C22.2 No. 94-91
UL
Certified by UL for use in Canada
IEC/EN 60947-5-1

CATALOG NOTES	0
----------------------	---

MODEL CODE	SL7-FL24-R
-------------------	------------



Powering Business Worldwide

Cechy i funkcje

COLOR	Red
ENCLOSURE COLOR	Black
FUNCTIONS	Flash light
LIGHT MODULES	LED
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)

Dane techniczne

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	NEMA 4X IP66
FLASHING FREQUENCY	1.4 Hz
FREQUENCY RATING	1.4 Hz
LIFESPAN, ELECTRICAL	100,000 h
LIGHT TYPE	Strobe light
MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RADIATION ANGLE	360 °
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
TYPE	Strobe light module
VOLTAGE TYPE	AC/DC

Klimatyczne warunki środowiskowe

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Parametry elektryczne

LEAKAGE CURRENT	0.003 A
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC -	24 V

Do pobrania

DEKLARACJE ZGODNOŚCI

[eaton-continuous-light-
module-declaration-of-
conformity-
eu250556en.pdf](#)

[eaton-continuous-light-
module-declaration-of-
conformity-
uk251039en.pdf](#)

INSTRUKCJE MONTAŻU

[IL047004ZU](#)

MODELE ECAD

[ETN.171404.edz](#)

MODELE MCAD

[DA-CD-sl7_bfl7](#)

[DA-CS-sl7_bfl7](#)

RYSUNKI

[eaton-operating-
dimensions-005.eps](#)

[eaton-operating-sl7-
strobe-light-module-
symbol.eps](#)

[eaton-operating-button-
symbol-009.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:

**Eaton Corporation plc**

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie prawa zastrzeżone.

Follow us on social media to get the latest product and support information.

