


# Specyfikacje



## Eaton C22G100

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 100 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series low voltage cylindrical fuse
<b>CATALOG NUMBER</b>	C22G100
<b>EAN</b>	5027590495196
<b>UPC</b>	051712754514
<b>PRODUCT LENGTH/DEPTH</b>	58 mm
<b>PRODUCT HEIGHT</b>	22.2 mm
<b>PRODUCT WIDTH</b>	22.2 mm
<b>PRODUCT WEIGHT</b>	55.3 g
<b>COMPLIANCES</b>	CE Marked GoST-R RoHS Compliant
<b>CERTIFICATIONS</b>	IEC 60269

## Electrical data

<b>AMPERAGE RATING</b>	100 A
<b>VOLTAGE RATING</b>	500 V
<b>VOLTAGE TYPE</b>	AC
<b>BREAKING CAPACITY</b>	120 kA
<b>CLASS</b>	Class C gL/gG
<b>FREQUENCY RATING - MAX</b>	62 Hz

## Compatible fuse holder

<b>SUITABLE FOR</b>	CH22 Modular fuse holder
---------------------	--------------------------

## Do pobrania

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf](#)

## DEKLARACJE ZGODNOŚCI

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATA:**



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Irlandia  
Eaton.com

Follow us on social media to get the latest product and support information.

