

# Specyfikacje



## Eaton C14G4

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 4 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series low voltage cylindrical fuse
<b>CATALOG NUMBER</b>	C14G4
<b>EAN</b>	5027590494052
<b>UPC</b>	051712754330
<b>PRODUCT LENGTH/DEPTH</b>	51 mm
<b>PRODUCT HEIGHT</b>	14.3 mm
<b>PRODUCT WIDTH</b>	14.3 mm
<b>PRODUCT WEIGHT</b>	20.3 g
<b>COMPLIANCES</b>	CE Marked GoST-R RoHS Compliant
<b>CERTIFICATIONS</b>	IEC 60269



Powering Business Worldwide

## Electrical data

AMPERAGE RATING	4 A
VOLTAGE RATING	690 V
VOLTAGE TYPE	AC
BREAKING CAPACITY	80 kA
CLASS	Class C gL/gG
FREQUENCY RATING - MAX	62 Hz

## Compatible fuse holder

SUITABLE FOR	CH14 Modular fuse holder
--------------	--------------------------

## Do pobrania

### DEKLARACJE ZGODNOŚCI

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf](#)

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Irlandia  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.