

Specyfikacje



Eaton C14M8

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 8 Amps, 80 kA Breaking capacity, class aM, without indicator, compatible with a CH14 Modular fuse holder

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C14M8
EAN	5027590495011
UPC	051712754668
PRODUCT LENGTH/DEPTH	51 mm
PRODUCT HEIGHT	14.3 mm
PRODUCT WIDTH	14.3 mm
PRODUCT WEIGHT	20.3 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269
MODEL CODE	CYLINDRICAL FUSE 14 x 51 8A AM 690V AC

Electrical data

AMPERAGE RATING	8 A
VOLTAGE RATING	690 V
VOLTAGE TYPE	AC
BREAKING CAPACITY	80 kA
CLASS	Class aM
FREQUENCY RATING - MAX	62 Hz

Compatible fuse holder

SUITABLE FOR	CH14 Modular fuse holder
---------------------	--------------------------

Do pobrania

DEKLARACJE ZGODNOŚCI

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Follow us on social media to get the latest product and support information.

