

## Data sheet

6AV2181-5AF10-0AX0



Figure similar

connection cable PN for KTPX00(F) Mobile (PROFINET) length: 10 m, scope of supply: 1 connection cable

| General information                               |                  |
|---|------------------|
| Product type designation                          | Connecting cable |
| Standards, approvals, certificates                |                  |
| CE mark   | Yes              |
| cULus   | Yes              |
| RCM (formerly C-TICK)                             | Yes              |
| KC approval                                       | Yes              |
| Suitable for safety functions                     | Yes              |
| Ambient conditions                                |                  |
| Ambient temperature during operation              |                  |
| • min.  | 0 °C             |
| • max.  | 55 °C            |
| Ambient temperature during storage/transportation |                  |
| • min.  | -20 °C           |
| • max.  | 60 °C            |
| Cables  |                  |
| Cable length                                      | 10 m             |
| Maximum tensile load                              | 300 N            |
| Color of cable sheath                             |                  |
| • green   | Yes              |
| Scope of supply                                   |                  |
| Delivery quantity in pieces                       | 1                |
| Other   |                  |
| Merchandise                                       | Yes              |
| Manufacturer name                                 | On request       |
| Usable in the following products                  |                  |
| • Product 1                                       | 6AV2125-*        |

last modified:

5/22/2024