

product description

PROFIBUS bus connector, RS 485, screw, with PG socket, 90°
SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90°
cable outlet, 15.8x 64x 35.6 mm (WxHxD), terminating resistor with
isolating function, With PG receptacle



transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
type of electrical connection	
• for PROFIBUS cables	Screw
• for network components or terminal equipment	9-pin Sub-D connector
type of electrical connection / FastConnect	No
mechanical data	
design of terminating resistor	Integrated resistor combination that can be selected with slide switch
material / of the enclosure	plastic
locking mechanism design	Screw
design, dimensions and weights	
type of cable outlet	90 degree cable outlet

width	15.8 mm
height	64 mm
depth	35.6 mm
net weight	10 g

ambient conditions

ambient temperature	
• during operation	0 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
protection class IP	IP20

product features, product functions, product components / general

product feature	
• silicon-free	Yes
product component	
• PG connection socket	Yes
• strain relief	Yes

standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• reference code / acc. to DIN EN 81346-2	XF

last modified: 08/30/2020