

MN - undervoltage release - 277 V AC 60 Hz - for TeSys GV4

TeSys GV electrical trip unit, MN undervoltage release, 277V AC 60Hz, for motor circuit breakers GV4. Opening of the the circuit breaker is ensured when the control voltage drops below 0.35 U_c , and possible between 0.35-0.7 U_c . Closing of the circuit breaker is possible when the control voltage is in limits 0.85-1.1 U_c . To be plugged inside the circuit breaker, connection by spring terminals. Multi standards certified (IEC, UL, CSA), Green Premium compliant (RoHS/REACH).

Informacje ogólne

Nazwa producenta	Schneider Electric
ID produktu wg producenta	GV4AU286
Seria produktu	TeSys GV4

Opis ETIM

Klasa	Wyzwalacz podnapięciowy (EC001022)
Grupa	Urządzenia niskonapięciowe (EG000017)
Znamionowe napięcie sterowania U_s dla AC 50 Hz	Nie dotyczy
Znamionowe napięcie sterowania U_s dla AC 60 Hz	277..277 V
Znamionowe napięcie sterowania U_s dla DC	Nie dotyczy
Rodzaj napięcia sterowania	AC
Rodzaj połączenia elektrycznego	Zacisk sprężynowy
Liczba styków zwiernych	0
Liczba styków rozwiernych	0
Liczba styków przełącznych	0
Zwłoczny	Nie
Do wyłącznika	Tak
Do łącznika krzywkowego	Nie
Do wyłącznika silnikowego	Nie
Do przekaźnika przeciążeniowego	Nie