



Zacisk szczękowy 95-300mm<sup>2</sup>, do 20x5-30x10

Typ  
Catalog No.      **AKS300**  
                             **107196**

## Program dostaw

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                |    |                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Asortyment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |    | System 60-mm<br>System 185-mm                                                                                                                                                                                                                                                                                                    |
| Funkcja podstawowa                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                |    | Technika przyłączy i połączeń                                                                                                                                                                                                                                                                                                    |
| Grupa asortymentowa                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                |    | Zaciski szczękowe                                                                                                                                                                                                                                                                                                                |
| Opis                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                |    | Bezdotykowa technika połączeń na szynach zbiorczych<br>Styknięcie przewodu z szyną zbiorczą odbywa się poprzez łożo kablowe                                                                                                                                                                                                      |
| Szerokość                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                | mm | 41                                                                                                                                                                                                                                                                                                                               |
| Znamionowy prąd pracy                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | I <sub>e</sub> | A  | 600                                                                                                                                                                                                                                                                                                                              |
| Przewód                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                |    | 95 - 300 mm <sup>2</sup><br>MCM300 - MCM600.<br>zaciskane bezpośrednio:<br>   |
| Cu factor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                | kg | 0,00                                                                                                                                                                                                                                                                                                                             |
| Stosowane do                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                |    | 20 x 5/10<br>25 x 5/10<br>30 x 5/10                                                                                                                                                                                                                                                                                              |
| Stosowane do                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                |    | Double T profile                                                                                                                                                                                                                                                                                                                 |
| <b>Wskazówki</b><br><input type="radio"/> round conductor, solid<br> Flexible, round conductor with correctly crimped ferrule<br>Round conductor, stranded<br> Section conductor, solid<br>Sector conductor, stranded<br># CU band<br> CU busbar |                |    |                                                                                                                                                                                                                                                                                                                                  |

## Aprobaty

|                                      |  |  |                                                   |
|--------------------------------------|--|--|---------------------------------------------------|
| Product Standards                    |  |  | UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking |
| UL File No.                          |  |  | E307559                                           |
| UL Category Control No.              |  |  | NMTR2, NMTR8                                      |
| CSA File No.                         |  |  | 236217                                            |
| CSA Class No.                        |  |  | 3211-37                                           |
| North America Certification          |  |  | UL recognized, CSA certified                      |
| Conditions of Acceptability          |  |  | Refer to approbation report                       |
| Specially designed for North America |  |  | No                                                |
| Suitable for                         |  |  | Feeder circuits                                   |
| Current Limiting Circuit-Breaker     |  |  | Refer to approbation report                       |
| Max. Voltage Rating                  |  |  | 600 V AC                                          |
| Degree of Protection                 |  |  | Feeder circuits                                   |

