PRODUCT DATASHEET

NiMH Battery Charger (CHEUF)

EMEA Region

Download Instructions (multilingual)

Product Detail:

Designation: Universal Charger Color: Black Charging Current: 2 or 4 "AA-C-D" 650mA

2 or 4 "AAA" 400mA

1 or 2 "9V" 17mA

Note: Batteries must be charged in pairs with the exception

of "9V" batteries that can be charged individually

Charging Times:	Battery	Capacity	Estimated
(estimated)	(NiMH)	(mAh)	(time)
	AA	1300-2000	3-4 hrs
	AA	2000-2300	4-5 hrs
	AAA	500-800	2-3 hrs
	C/D	2500	4 hrs
	9V	175	11 hrs

Shutoff Mechanism: Delta V Detection: 5mV per cell for "AA-AAA-C-D" Timer Control: 2 or 4 "AA-C-D" 5 hours 2 or 4 "AA" 3.5 hours AC Adapter Input: 100-240VAC, 50/60Hz, 8W AC Adapter Output: 12VDC, 600mA Trickle Charge: "AA-C-D" 50mA "AAA" 25mA Typical Weight: 322 grams Dimensions (mm): 65 x 180 x 130 (H x L x W) Safety Features: Short Circuit and Reverse Polarity Protection Primary Battery Detection Bad Battery Detection Delta V Charging Cut Off

Safety Timer to Prevent Overcharge

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication. Contents herein do not constitute a warranty.



Universal Charger

EMERGÍZER.

GAUGES BATTERY POWER

 Indicates amount of charge in the battery

ENSURES FULL CHARGE

Charges batteries to 100% capacity



MAXIMIZES PERFORMANCE

 Helps batteries retain capacity by preventing damage from overcharge



VERSATILE

 Charges AA, AA, C, D and 9V NiMH batteries



Before Using Your Charger: Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with *Energizer*[®] NiMH batteries.